

PA370 EXPRESS PU WOOD ADHESIVE

LOW ODOUR
LOW Nonshrinking
PRESS TIME Extremely
high bond strength
Conforms to D4 according to DIN EN 204



Low Clamping



Excellent Bonding



Fast Curing



Waterproof

Akfix®

Creates
Permanent
Solutions

www.akfix.com • info@akfix.com

PA370

EXPRESS PU WOOD GLUE

TRANSPARENT

PROPERTIES

Fast curing. Low press time. Transparent.
Extremely high bond strength on numerous substrates.
Conforms to D4 according to DIN EN 204. Easy to use.
Very good resistance to chemicals.
Excellent resistance to moisture and weather conditions.
Nonshrinking. Low odour. Useable in slightly wet substrates.

APPLICATION AREAS

Fixing and gluing wooden elements to other various porous and non-porous elements as wood, metal, concrete, polystyrene foam etc. Furniture and boat production. All bonding applications that need a high water resistance.



Low Clamping



Excellent Bonding



Fast Curing



Waterproof



twitter.com/AkfixSealants



youtube.com/user/AkfixSealants



instagram.com/AkfixSealants



vimeo.com/AkfixSealants

www.akfix.com



pinterest.com/Akfixsealants



plus.google.com/+AkfixSealantsAdhesives



facebook.com/AkfixSealantsAdhesives



linkedin.com/in/AkfixSealants

info@akfix.com