



# 915N

NEUTRAL  
WEATHERSEAL SILICONE

**HIGH UV  
RESISTANCE**

**Akfix®**

■ MASTER OF SOLUTIONS ■

**CREATES  
PERMANENT  
SOLUTIONS**

[www.akfix.com](http://www.akfix.com) / [info@akfix.com](mailto:info@akfix.com)



**Neutral cure, premium performance silicone sealant, exclusively created for weather sealing and glazing application. It forms highly resistive weatherproof seal on windows and building facades.**



- Provides permanent elasticity thanks to its 100% silicone formula,
- Not affected by exposure to sunlight, rain, snow and maintains it over many years,
- Exceptional resistance to temperature extremes,
- Very low odor and noncorrosive
- Excellent flexibility and adhesion to numerous porous and non-porous
- Substrates for large scale construction and glazing applications.
- Fast curing, low modulus, high elasticity. High viscosity non slump formula.



**ALL WEATHER  
RESISTANT**



## Consumption (approx.)

<b>Joint Width</b>	10mm	15mm	20mm
<b>Joint Depth</b>	6mm	8mm	10mm
<b>Efficiency /310 ml</b>	5meters	2,5meters	1,5meters

# Surface Preparation

Following cleaning procedure and materials are recommended:

- Glass**      Degrease with alcohol or MEK
- Aluminium, light alloys and stainless steel**      Degrease with alcohol or MEK
- Other Metals**      Lightly abrade then degrease as above
- Wood**      Lightly abrade surface then remove dust
- Plastics**      Degrease using an agent recommended by plastics manufacturer
- Concrete and other alkaline Surfaces**      Brush and remove dust



## Meets or exceeds the requirements of the following specifications:

- The French VOC requirements for class A+
- ISO 11600 F & G 20LM.
- CE marked for EN 15651 for façade, glazing and sanitary applications.
- The requirements of VOC content specifications in LEED credit EQc4.1 “Low-emitting products” of SCAQMD rule 1168.

