

# 702

## Super Glue Cyanoacrylate

### 1 - Description

Akfix 702 is an extra low viscosity superfast instant glue based on cyanoacrylate adhesive. It is excellent where extremely fast cure is required and/or where penetration is required.

### 2 - Properties & Features

- Immediate bond
- Very high bond strength after a few seconds.

### 3 - Fields of Application

Suitable for glass, rubber, metals, ceramic and many plastics.

### 4 - Product Information

Packaging	Gw 30 gr
Shelf Life	12 months
Storage Conditions	Store in cool and dry conditions between +5°C and +25°C

### 5 - Technical Data

	Method/Conditions	Value
Basis		Ethyl Cyanoacrylate
Consistency	ISO 7390	Liquid gel
Density	ISO 1183-1	1,05±0,01 g/ml
Color		Colorless
Flashpoint		> 80°C
Viscosity	ASTM D1084	2 – 5 Cps

### 6 - Directions for Use

Substrates need to be smooth and have a perfect connection area. Apply a drop on one of the substrates. Join substrates and press firmly for one minute. Application temperature is between +5°C and +30°C

### 7 - Remarks & Restrictions

- Cyanoacrylates should ideally be stored in original sealed containers until used.
- Avoid exposure to strong light and heat sources
- Cyanoacrylates can bond to skin within seconds
- Do not drip into skin or into eyes - can cause serious injury to your eyes.

### 8 - Safety

Ensure good ventilation of the work station. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety.

### 9 - Disclaimer

Rev no:0006 Rev Date: 24.10.2022

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.