

A119

PRE-FILLED SPRAY CAN

Description

Pre-Filled Spray Can is a spray can product that can be filled with cellulosic, acrylic and synthetic paint in the desired color by formulating with special gas and special solvents; It provides ease of application with its innovative spray and fine-wide jet atomization valve technology.

***It is prepared to be filled with paint filling machines. The expert dealer creates the ready-to-use final product by adding 100 ml of paint.**

Properties & Features

- Requires a special filling machine for filling.
- Easy to apply and saves time.
- Provides the option to fill in the desired color and quality.
- Provides the desired width of the spray regime thanks to the innovative nozzle and valve technique.
- Not suitable for water-based paints.
- Pre-filled Aerosol offers the feature of replacing the spray gun in small body shops when small parts need to be painted.
- No change in pressure while providing high efficiency.
- Pre-filled cans (400 ml) can be filled with up to 100 ml of paint

Product Information

Packaging	400ml
Shelf Life	24 months
Storage	At cool and dry ambient. 12°C to 21°C

Technical Data

Form	Liquid aerosol
Appearance	Transparent
Specific gravity	0,71 ± 0,01 gr/cm ³
Odor	Solvent
Colour	Varies depending on the paint being filled
Flammability	It is extremely flammable. Vapors are harmful and Flammable.

Directions for Use

- Be sure to read the instructions for use.
- Clean the surface to be applied from all kinds of dirt, rust, moisture and wetness.
- Shake the can filled with paint for 1 minute before use.
- Perform preliminary tests and compatibility tests for filled paint applications before application.
- Clean the surface if there are old paint residues and rust. If necessary, sand and apply primer. Wait for it to dry for 1-2 hours. Apply plastic primer on plastic parts.
- Apply the paint crosswise in thin layers from a distance of 25-30 cm.
- After the painting process is completed, turn the can upside down to clean the nozzle and prevent clogging. Hold the valve pressed until no paint comes out and perform the cleaning process. Otherwise, the paint accumulated in the valve and nozzle will freeze, making the product unusable.
- Drying time (20°C, 50% RH) depends on the ambient temperature, air humidity, thickness of the applied layer and the type of filled paint (see the paint manufacturer's information)



Remark & Restrictions

- Store in a cool and dry place.
- Avoid contact with eyes, rinse immediately with plenty of water and seek medical attention.
- In case of contact with skin, rinse with plenty of water.
- DO NOT BURN.
- DO NOT expose to excessive heat above 50°C.
- Keep away from sources of ignition and do not smoke.
- Do not spray on a flame or an incandescent object.
- Do not pierce, may explode, do not throw into fire.
- Test for suitability before use.
- Keep out of reach of children.

Safety

Ensure good ventilation of the work station. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety. Keep out of reach of children.

Disclaimer

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.