

# A114

## CARB & CHOKE CLEANER

### 1 - Description

**Akfix A114 Carb & Choke Cleaner;** is a fast-acting carburetor and choke cleaner that dissolves carburetor deposits such as sludge, gum and varnish. Its low VOC formula is designed to maximize carburetor performance, improve fuel system performance and ensure maximum fuel economy.

### 2 - Properties

- Makes the engine run smoother.
- Ideal for all types of automotive engines such as cars, trucks, marine engines.
- Improves fuel system performance. ensures maximum fuel economy.
- Does not leave a sticky residue,
- Efficiently cleans soil, gum and varnish.
- Will not harm oxygen sensors or catalytic converters.
- The aerosol can be used in 360 degrees.

### 3 - Application Areas

- Cleaning automatic chokes,
- Carburetor elements,
- Intake parts and ventilating systems,
- Suitable for general purpose cleaning of non-painted surfaces.

### 4 - Product Information

Packaging	400 ml, 500 ml
Shelf Life	36 months
Storage Conditions	Stored between +5°C to +25°C

### 5 - Technical Data

Parameter	Conditions/Parameters	Value
Form		Aerosol
Odor		Solvent
Color		Colorless liquid
Specific weight		0,824 gr/ml

## 6 – Directions for Use

Read all directions before using this product. Use plastic extension tube to direct spray to exact location.

### Carburetor and Linkage

- With ignition off and engine cool, remove air filter and entire exterior surface of carburetor including linkage.
- After carburetor dries, start engine and spray Akfix A114 down the carburetor throat to remove the deposits from the lower throttle plate area.

### Automatic Chokes

- With engine off, spray Akfix A114 on both ends of choke valve and corresponding linkages while opening and closing choke by hand.

### Manifold Heat Control Valve

- With engine cold, spray Akfix A114 on both ends of heat control valve shaft.
- Move counterweight up and down until valve moves freely. If necessary, tap gently with a light hammer to loosen a frozen heat control valve.

### PCV Valves

- Disconnect crank case side of PCV valve and, with the engine running, spray CRC Carb & Choke Cleaner into open end of valve while working the plunger back and forth.

### Important

- If spilled or sprayed on painted surface, wipe off or wash off immediately.

## 7 –Remarks & Restrictions

- The can is pressurized.
- Keep away from direct sunlight.
- Keep away from sources of ignition.
- Use only in well-ventilated areas.
- Keep out of reach of children.

## 8 –Safety

Ensure good ventilation of the work station. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety. Keep out of reach of children.

## 9 –Disclaimer

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information

in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.