



## AKFIX A120 CAR UNDERBODY PROTECTION (ANTIGRAVEL)

### 1 – DESCRIPTION

**Akfix A120 Car Underbody Protection** is a modified alkyd resin-based surface protectant, especially developed for the protection of areas where automobiles and commercial vehicles can be exposed to various impacts such as stone bumps.

### 2 – PROPERTIES

- Creates a hard, textured surface that prevents chips and abrasions from stones and impurities.
- Compatible with OEM textures.
- Very high wear resistance.
- Suitable for oven drying.
- Easy sanding after drying.

### 3 – APPLICATION AREAS

- Can be applied on steel, aluminum, galvanized surfaces, stainless steel, plastic and epoxy coated surfaces.
- Protecting the wheel wells, rocker panels and undercarriage from inevitable wear and keeping the original appearance.

### 4 - INSTRUCTIONS

- Shake can well before use.
- The application surface must be dry and free of rust, dirt and grease.
- Old coating mass should be removed.
- Can be painted over with all paint systems after approx. 12 hours (depending on coating thickness), especially with water-based paints.
- Thinning the product causes runoff and reduction of rough effect.
- Optimum spraying distance is 30 cm.
- Working pressure: 3 - 6 bar.

### 5- PACKAGING

Product	Weight	Package
Black, White, Grey	1 kg	12

### 6- STORAGE AND SHELF LIFE

Can be stored for 12 months at 20 ° C in its original sealed package.



## 7- TECHNICAL PROPERTIES

<b>Chemical Structure</b>	: Modified Alkyd Resin
<b>Density</b>	: 0,97 g/cm <sup>3</sup>
<b>Surface Dry Time</b>	: 1 hour
<b>Color</b>	: Black, White, Grey

## DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.